

GNSS ANTENNA

NGA100



- Part No.: NGA100-10, NGA100-20, NGA100-30
- Receiving Frequency: 1575 MHz \pm 5 MHz
- Polarization: Circular
- Antenna Gain: \geq 3.5 dBi
- Noise Figure: \leq 1.5 dB
- Power Supply: DC 3 V/5 V
- Max. Diameter: Φ 96 mm
- Length: 126 mm
- Cable: RG58 10 m, 20 m, 30 m
- Connector: TNC or BNC
- Operating Temperature: -40°C \sim +55°C
- IP Grade: IP66

VHF ANTENNA

NVA100



- Frequency Range: 155MHz \sim 163MHz
- Polarization: Vertical
- Gain: 3.5dBi
- VSWR: 1.2
- Impedance: 50 Ω
- Length: 1.38 m
- Connector: PL259
- Rod Antenna: Fiberglass Epoxy
- Wind Resistance: 60m/s
- Max TX Power: 100W
- Operating Temperature: -40°C \sim +55°C
- IP Grade: IP66

NAVTEX ANTENNA

NXA200

NXA200 Antenna can be used for NAVTEX receivers of most brands.



- RX Frequency: 518 kHz, 490 kHz, 4209 kHz
- Bandwidth: 504 kHz \pm 20 kHz, 4209.5 kHz \pm 100 kHz
- Radiation Pattern: Omni-directional
- Polarization: Vertical
- Impedance: 50 Ω / TNC
- Cable Length: 20 m RG58
- Input Voltage: 7 \sim 9 V
- Temperature Range: -40°C \sim +55°C
- Size: Φ 150 \times 230 (H) mm
- Weight: 1.3 kg (including cable)
- IP Grade: IP66